

Georgian Bay Reinforcement Fabrics

999 William Street, PO Box 459, Midland Ontario L4R 4L3 Tel. 705-527-5404 Fax. 705-527-0258

MATERIAL SAFETY DATA SHEET

Section 1: Product and Preparation Information

Date: April 30, 2014
Product Name: T1844-A00,

Synonyms: None

Product Use: Fiberglass Textile Reinforcement WHMIS Classification: Non-Regulated Manufactured Article

Manufacturer: Georgian Bay Reinforcement Fabrics

999 William Street, P.O. Box 459

Midland, Ontario

L4R 4L3

Telephone: 705-527-5404 Fax: 705-527-0258

Section 2: Composition and Hazardous Ingredient Information

Section 2. Composition and mazaradus inficarent information			
<u>Ingredient</u>	CAS#	ACGIH TLV	OSHA PEL
		(8-hr TWA)	(8-hr TWA)
Fiber Glass Continuous Filament:			
- Nonrespirable fibers and particulate	65997-17-3	5 mg/m⊡	15 mg/m △
		(Inhalable fraction)	(Total dust)
- Respirable particulate		3 mg/m⊡	5 mg/m⊡
		(PNOC*)	(Respirable dust)
- Respirable particulate with fiber like-		1 fiber/cc	None Established
dimensions (glass shards)		aspect ratio >5:1	

^{*}PNOC = Particles not otherwise classified.

As manufactured continuous filament glass fibers are not respirable. Continuous filament glass products that are chopped, crushed or severely mechanically processed during manufacturing or use may contain a very small amount of respirable particulate, some of which may be glass shards.

Section 3: Physical Data and Chemical Properties

Vapour Pressure (mm Hg @ 20°C):Not ApplicablepH:Not ApplicableVapour Density (Air = 1):Not ApplicableBoiling Point:Not ApplicableEvaporation Rate:Not ApplicableViscosity:Not Applicable

Specific Gravity (Water=1): 2.60 Appearance: Woven Fiberglass Fabric

Solubility in Water: Insoluble Physical State: Solid

Freezing Point: Not Applicable Odour (Threshold): None (Not Applicable)



Section 4: Fire or Explosion Hazard

Flash Point: None Flammability Limits (%): None

Auto Ignition Temperature: Not Applicable

Extinguishing Media: Water, Foam, Carbon Dioxide or Dry Chemical.

Unusual Fire and Explosion Hazards: None Known

Fire Fighting Instructions: Fire fighters should wear appropriate protective equipment

including Self Contained Breathing Apparatus (SCBA).

Hazardous Combustion Products: Primary combustion products are carbon monoxide, carbon dioxide

and water. Other undetermined compounds could be released in

small quantities.

Section 5: Stability and Reactivity Data

Stability: Stable **Incompatible Materials and Conditions to Avoid:** None

Hazardous Decomposition Products: Sizings or binders may decompose in a fire. See

Section 4 of MSDS for Hazardous Combustion

Products statement.

Hazardous Polymerization: Will not occur.

Section 6: Toxicological Properties (Health Hazards)

Acute Effects:

Inhalation: Fiber glass continuous filament is a mechanical irritant. Breathing dusts and fibers may cause

short term irritation of the mouth, nose and throat.

Skin: Skin contact with dust and fibers may cause itching and short term irritation.

Eyes: Eye contact with dust and fibers may cause short term mechanical irritation or damage.

Ingestion: Ingestion may cause short term mechanical irritation of the stomach and intestines. Observe

individual, if symptoms develop, consult a physician.

Chronic Effects: The International Agency for Research on Cancer (IARC) has classified Continuous

Filament Fiber Glass under Group 3: Not Classifiable with respect to Human

Carcinogenicity.

Section 7: Preventive Measures (Personal Protection)

Respiratory Protection: Where dust levels exceed the TLV, use an NIOSH/MSHA approved disposable

dust respirator. Use respiratory protection in accordance with your company's

respiratory protection program.

Ventilation: General dilution ventilation and/or local exhaust ventilation should be provided as

necessary to maintain exposures below occupational exposure limits.



Skin Protection: Loose fitting long sleeved shirt that covers to the base of the neck, long pants and

gloves.

Eye Protection: Safety glasses.

Section 8: First Aid Measures

Inhalation: Move person to fresh air. Seek medical attention if irritation persists.

Eye Contact: Flush eye with running water for at least 15 minutes. Seek medical attention if irritation persists. **Skin Contact:** Wash with mild soap and running water. Use a washcloth to help remove fibers. Do not rub or

scratch affected areas. Seek medical attention if irritation persists.

Ingestion: Ingestion of this material is unlikely. If it does occur, watch the person for several days to make

sure that intestinal blockage does not occur.

Section 9: Release and Disposal Procedures

Waste Disposal: Dispose of Fiberglass as dry garbage as per local, provincial/state and federal regulations.

Release (Spill/Leak): Use a vacuum cleaner to clean up glass fibers. Do not use an air hose.

Work and Hygienic Practices: Handle using good industrial hygiene and safety practices. Avoid

unnecessary exposure by using adequate local exhaust ventilation. Remove material from the skin and eyes after contact. Remove material from clothing using vacuum equipment (never use compressed air). Always wash work clothes separately from other clothing. Wipe out the washer or sink to prevent loose glass fibers from getting on other clothing.

Keep the work area clean of dusts and fibers released during processing or fabrication. Use vacuum equipment to clean up product. Avoid dry seeping or using compressed air as these techniques re-suspend dusts and fibers into the air. Have access to safety showers and eye wash stations.

Section 10: Handling and Storage

General: No special storage or handling procedures is required for this material. It is recommended to

store in a cool, dry place.

Section 11: Transport Information

Proper Shipping Name: Material is non-regulated

TDG Hazard Classification: Primary – None Secondary - None