



## ANCAREF PRODUCT SPECIFICATION

Issued: June 2016  
Revised: January 2023

Product: **ANC-CU-390-xxx**

|                    | <u>Metric</u>                          | <u>SAE</u>                                  |
|--------------------|--|---|
| Style:             | ANC-CU                                 | ANC-CU                                      |
| Finish:            | A03<br>(Epoxy Resin Compatible)        | A03   |
| Pattern:           | Uni-Directional                        | Uni-Directional                             |
| Construction:      | Warp: 48/10cm (+/- 1)<br>Weft: veil    | 12.0 /inch (+/- 0.3) ASTM D-3775<br>veil    |
| Yarn               | Warp: 12k carbon (T700S)<br>Weft: veil | 12k carbon (T700S)<br>veil                  |
| Weight             | 388 g/m <sup>2</sup> (+/-5%)           | 11.5 oz/yd <sup>2</sup> (+/-5%) ASTM D-3776 |
| Thickness:         | 0.36 mm (+/-0.01)                      | 0.014 inches (+/-0.002) ASTM D-1777         |
| Packaging<br>Core: | 150 mm ID Core                         | 6.0 inch ID Core                            |
| Available Widths:  | 25 - 610 mm                            | 1 - 24 inches                               |

*All values above are nominal and are to be used as guidelines.*

*Although all statements are believed to be accurate and reliable, they are presented without guarantee or responsibility on our part.*